

# Nikon AP-8 / AC-2S / AX-2S Series Automatic Levels

## Specifications Sheet

	AP-8	AC-2S	AX-2S
<b>Telescope</b>			
Tube length	190 mm (7.5 in)	190 mm (7.5 in)	190 mm (7.5 in)
Image	erect	erect	erect
Magnification	28x	24x	20x
Effective diameter of objective lens	30 mm (1.2 in)	30 mm (1.2 in)	30 mm (1.2 in)
Field of view	1°30'(2.6 ft @ 100 ft)	1°30'(2.6 ft @ 100 ft)	1°30'(2.6 ft @ 100 ft)
Minimum focusing distance	0.75 m (2.46 ft)	0.75 m (2.46 ft)	0.75 m (2.46 ft)
Stadia ratio	1:100	1:100	1:100
Stadia additive constant	0	0	0
<b>Level Vial Sensitivity</b>			
Circular level	10/2 mm	10/2 mm	10/2 mm
<b>Standard Deviation</b>			
(1 km double-run leveling) Without micrometer	±1.5 mm	±2.0 mm	±2.5 mm
<b>Automatic Compensator</b>			
Type	wire-hung, magnetic damper	wire-hung, magnetic damper	wire-hung, magnetic damper
Compensation range	±16'	±16'	±16'
Setting accuracy	±0.5"	±0.5"	±0.5"
<b>Horizontal Circle</b>			
Diameter of circle	110 mm (4.3 in)	110 mm (4.3 in)	110 mm (4.3 in)
Minimum increment	1°/1 g	1°/1 g	1°/1 g
Reading estimation	0.1°/0.1g	0.1°/0.1g	0.1°/0.1g
<b>Dimensions</b>			
Instrument (L x H x W)	190 x 128 x 123 mm (7.5 x 5.0 x 4.8 in)	190 x 128 x 123 mm (7.5 x 5.0 x 4.8 in)	190 x 128 x 123 mm (7.5 x 5.0 x 4.8 in)
Carrying case	292 x 170 x 163 mm (11.5 x 6.7 x 6.4 in)	292 x 170 x 163 mm (11.5 x 6.7 x 6.4 in)	292 x 170 x 163 mm (11.5 x 6.7 x 6.4 in)
<b>Weight</b>			
Instrument	1.25 kg (2.8 lb)	1.25 kg (2.8 lb)	1.25 kg (2.8 lb)
Carrying case	1.2 kg (2.7 lb)	1.2 kg (2.7 lb)	1.2 kg (2.7 lb)



**SIMPLE • ACCURATE • VALUE**

Spectra Precision Authorized Dealer

